

# VTL-145-F



**Van Mounted  
Telescopic Platform**

**Keeping you safe whilst  
maximising productivity.**

# VTL-145-F | VAN-MOUNTED

## Technical Specifications

Working Height	14.6m
Platform Height	12.6m
Outreach	9.2m
Gross Vehicle Weight (GVW)	5200kg
Payload*	1500kg
Bucket Capacity	230kg
Flyboom	140°
Lift Rotation	360°
Height	3460mm
Length	7309mm
Wheelbase	3520Lmm
Slope Longitudinally	10°
Slope Sideways	5°
Outriggers	A-Frame

Technical information is subject to change without prior notice. \*Depending on the vehicle and subject to options fitted. Max payload after driver, passenger and fuel subject to options fitted.

## Standard Equipment

- A "bestseller" with great payload.
- Ultra-high strength steel boom with integrated boom wear pads.
- Emergency lowering controls in pedestal.
- LMC load sensing system.
- Knuckle/turret tail swing, and A-frame outriggers within the mirrors.
- Under-mounted bucket.

## Options and Accessories

- Bespoke storage racking
- Twin joystick LMC control system with LCD interface screen
- Walk-in or Duck-under bucket
- 1kV certified insulation
- Chapter 8 compliance
- Stabiliser controls from bucket
- Slew rotation interlock
- Reversing camera
- Bucket rotator - 2 x 90° (reduced outreach)
- Limited working area without outriggers
- Optional 420° rotation

## Vehicle Options



Contact us for full vehicle list.

## Diagrams

