

VTM-170 F



**Van Mounted
Telescopic Platform**

**Keeping you safe whilst
maximising productivity.**

VTM-170-F | VAN-MOUNTED

Technical Specifications

Working Height	17m
Platform Height	15m
Outreach	10.5m
Gross Vehicle Weight (GVW)	7000kg
Payload*	2200kg
Bucket Capacity	230kg
Flyboom	140°
Lift Rotation	360°
Height	3700mm
Length	8465mm
Wheelbase	4100mm
Slope Longitudinally	10°
Slope Sideways	5°
Outriggers	A-Frame

Technical information is subject to change without prior notice. *Depending on the vehicle and subject to options fitted. Max payload after driver, passenger and fuel subject to options fitted.

Standard Equipment

- The most precise control system on the market
- LMC controls with variable outreach
- Emergency lowering controls in pedestal
- Knuckle/turret tail swing within the mirrors
- Outriggers within the mirrors
- Ultra-high strength steel boom delivers exceptional rigidity
- Class leading leftover payload

Options and Accessories

- Bespoke storage racking
- Twin joystick LMC control system with LCD interface screen
- Walk-in or Duck-under bucket
- 1kV certified insulation
- Chapter 8 compliance
- Stabiliser controls from bucket
- Slew rotation interlock
- Reversing camera
- Bucket rotator - 2 x 90° (reduced outreach)
- Optional 420° rotation

Vehicle Options

IVECO

Contact us for full vehicle list.

Diagrams

