

VST-40-MHI



**Insulated Telescopic
Platform**

**Keeping you safe whilst
maximising productivity.**

VST-40-MHI | INSULATED

Technical Specifications

▶ Working Height*	14.8m
▶ Platform Height	12.8m
▶ Outreach	8.5m
▶ Articulated Lower Boom	0° to 80°
▶ Main Boom	-25° to 80°
▶ Flyboom	180°
▶ Lift Rotation	360°
▶ Max. Material Handling	455kg
▶ Slew Rotation	360° cont.
▶ Electric Insulation	Up to 46kV
▶ Outriggers	A-Frame

As our insulated platforms can be configured and specified to customer requirements, please contact Versalift direct to discuss your particular situation and operation conditions

*Technical information is subject to change without prior notice. *Depending on the vehicle and subject to options fitted.*

Standard Equipment

- CAT C - 46kV insulated for live working (ANSI A92.2)
- Telescopic insulated platform
- Lower boom capable of 80° operation
- Full pressure hydraulic single lever upper controls
- A-frame outriggers to rear
- Aluminium flatbed
- Manual operated jib
- Emergency pump system
- Emergency stop at platform and pedestal
- Full functions at ground
- Torqued and sealed critical fasteners
- 4 x outrigger spreader pads with carrying frames
- Protective covers for insulated booms

Options and Accessories

- 69kV insulation
- Material Handling (MH) jib and winch capability up to 455kg
- Hydraulic operated jib
- Radial outriggers to front (subject to platform type)
- Bespoke aluminium toolboxes
- Bespoke fibreglass GRP lockers
- Earth grounding cable
- Thermostatically controlled locker heaters
- Hydraulic pressure intensifier
- Chapter 8 compliance

Vehicle Options



Mercedes-Benz

Diagrams

